

## The Improved Biofuel Cell for Electrical Power Generation from Wastewaters

**Authors :** M. S. Kilic, S. Korkut, B. Hazer

**Abstract :** Newly synthesized Polypropylene-g-Polyethylene glycol polymer was first time used for a compartment-less enzymatic fuel cell. Working electrodes based on Polypropylene-g-Polyethylene glycol were operated as unmediated and mediated system (with ferrocene and gold/cobalt oxide nanoparticles). Glucose oxidase and bilirubin oxidase was selected as anodic and cathodic enzyme, respectively. Glucose was used as fuel in a single-compartment and membrane-less cell. Maximum power density was obtained as 0.65 nW cm<sup>-2</sup>, 65 nW cm<sup>-2</sup>, and 23500 nW cm<sup>-2</sup> from the unmediated, ferrocene and gold/cobalt oxide modified polymeric film, respectively. Power density was calculated to be ~16000 nW cm<sup>-2</sup> for undiluted wastewater sample with gold/cobalt oxide nanoparticles including system.

**Keywords :** bilirubin oxidase, enzymatic fuel cell, glucose oxidase, nanoparticles

**Conference Title :** ICEBESE 2015 : International Conference on Environmental, Biological, Ecological Sciences and Engineering

**Conference Location :** Prague, Czech Republic

**Conference Dates :** March 23-24, 2015