

An Approximate Engineering Method for Aerodynamic Heating Solution around Blunt Body Nose

Sahar Noori, Seyed Amir Hossein, and Mohammad Ebrahimi

Abstract—This paper is devoted to predict laminar and turbulent heating rates around blunt re-entry spacecraft at hypersonic conditions. Heating calculation of a hypersonic body is normally performed during the critical part of its flight trajectory. The procedure is of an inverse method, where a shock wave is assumed, and the body shape that supports this shock, as well as the flowfield between the shock and body, are calculated. For simplicity the normal momentum equation is replaced with a second order pressure relation; this simplification significantly reduces computation time. The geometries specified in this research, are parabola and ellipsoids which may have conical after bodies. An excellent agreement is observed between the results obtained in this paper and those calculated by others' research. Since this method is much faster than Navier-Stokes solutions, it can be used in preliminary design, parametric study of hypersonic vehicles.

Keywords—Aerodynamic Heating, Blunt Body, Hypersonic Flow, Laminar, Turbulent.

I. INTRODUCTION

THE preliminary thermal design of hypersonic vehicles requires precisely and reliably predicting the convective heating over the blunt nose of the vehicle, since aerodynamic heating is a function of V_∞^3 , its consideration in hypersonic flights is more important than aerodynamic forces. Therefore in high speeds the first concern is the large amount of heat production on the surface of vehicle which highly increases the shell temperature.

Methods of solving aerodynamic heating can be the result obtained by numerically solving the Navier-Stokes (NS) equations [1-3], or one of their various subsets such as the parabolized Navier-Stokes (PNS) equations [4-5] and viscous shock layer (VSL) equations [6-9] for the flow field surrounding the vehicle. But these methods require a large computer run times and storage, and are not generally applicable to parametric studies or preliminary design calculations.

Two of the simpler engineering aerodynamic heating methods that are currently used are AROHEAT [10], and

INCHES [11]. AEROHEAT calculates approximate surface streamlines based on solely on the body geometry, and assumes modified Newtonian theory which is inaccurate for slender bodies. INCHES used of an axisymmetric Maslen technique and an approximate expression for the scale factor in the windward and lee ward planes which describes the spreading of surface streamlines. Another approximate solution for convection heating rate is the LATCH (Langley Approximate Three dimensional Convective Heating) code [12] which provides reasonably accurate heating rates over most of the re-entry vehicles.

In this paper an approximate method has been developed for solving the inverse problem of inviscid perfect gas flow over blunt bodies at zero angle of attack. The procedure is of an inverse nature, that is, a shock wave is assumed and calculations proceeded between the shock and body, until the calculation of all properties after shock. For simplicity, the normal momentum equation is replaced with a Maslen second order pressure equation [13]; this simplification significantly reduces machine computation time and cause resolve simplicity. On the other hand, used to the commercial CFD code for flow field solution. The numerical simulations are able to generate large amount of data that describes the fluid flow, using information from each node and every cell of the grid that models the fluid domain. So, since the grid is sufficiently dense, unstructured mesh, the flow can be reconstructed and the flow features extracted and analyzed. To predict laminar and turbulent surface heating rates, Zoby's convective-heating approximate equation has been used [14]. The method provides a rapid technique such as parabola and ellipsoids.

An excellent agreement is observed between the results obtained in this paper and those calculated by others' research. Since this method is much faster than Navier-Stokes solutions, it can be used in preliminary design, parametric study of hypersonic vehicles and predict axisymmetric viscous hypersonic flows.

II. ANALYSIS

In this paper, the procedure is of an inverse nature that is assuming a shock-wave shape. In this research, Maslen's method is an inverse method, where a shock wave is assumed and calculations proceeded along rays normal to the shock somewhere between $0 < \varphi$. (Fig 1) The solution is iterated until the given body is computed. The inverse method is applied for the calculation of flow field between the shock

Sahar Noori is with the Aerospace Institute, Shahrak ghods, Tehran, Iran (phone: +98-021-88366030; fax: +98-021-88362011; e-mail: noori@ari.ac.ir).

Seyedamir Hosseini with the Aerospace Institute, Shahrak ghods, Tehran, Iran (phone: +98-021-88366030; fax: +98-021-88362011; e-mail: seyedamir.hosseini@yahoo.com).

Mohammad Ebrahimi with the Aerospace Institute, Shahrak ghods, Tehran, Iran (phone: +98-021-88366030; fax: +98-021-88362011; e-mail: mebrahimi@ari.ac.ir).

wave and the body surface. Calculation body with the analysis body has contrasted and according to the entire errors between them, the shape of shock with the coefficient scales has been approved.




Fig. 1 Shock shape model

The governing equations get use for calculation flow field.

Continuity:

$$\left(\frac{\partial(r^n \rho u)}{\partial x}\right)_y + \left(\frac{\partial(r^n \rho v)}{\partial y}\right)_x = 0 \quad (1)$$

X-momentum:

$$u\left(\frac{\partial u}{\partial x}\right)_y + v\left(\frac{\partial u}{\partial y}\right)_x - \frac{uv}{R_s} = -\frac{1}{\rho}\left(\frac{\partial P}{\partial x}\right)_y \quad (2)$$

Y-momentum:

$$u\left(\frac{\partial v}{\partial x}\right)_y + v\left(\frac{\partial v}{\partial y}\right)_x - \frac{uv}{R_s} = -\frac{1}{\rho}\left(\frac{\partial P}{\partial y}\right)_x \quad (3)$$

Entropy:

$$\left(\frac{\partial(r^n \rho u)}{\partial x}\right)_y + \left(\frac{\partial(r^n \rho v)}{\partial y}\right)_x = 0 \quad (4)$$

Assume that the shock layer is thin, and hence the streamlines are essentially parallel to the shock wave, here is the momentum equation normal to a streamline

$$\frac{\rho u^2}{R_s} = \frac{\partial p}{\partial \psi} \quad (5)$$

Define a stream function ψ , where R_s is the shock radius of curvature and replace stream function in equation (5) [introduce a von Mises transformation such that the independent variables are $((x, \psi)$ rather than (x, y)]

$$\frac{\rho u^2}{R_s} = \frac{\partial p}{\partial \psi} (\rho u) \quad (6)$$

Or

$$\frac{u}{R_s} = \frac{\partial p}{\partial \psi} \quad (7)$$

Where all the streamlines are essentially parallel to shock, the velocity just behind the shock, $u \approx u_s$. Thus equation (7) becomes

$$\frac{u_s}{R_s} = \frac{\partial p}{\partial \psi} \quad (8)$$

Integration equation 8 between appoint in the shock layer and just behind shock wave have

$$p(\psi) = p_s + \frac{u_s}{R_s r_s^n} (\psi - \psi_s) \quad (9)$$

III. AERODYNAMIC HEATING CALCULATIONS

The zoby's approximate convective heating equations are obtained from the integral form of the axisymmetric boundary layer momentum equation. The equations for laminar flow are as follows [14]

$$q_{wl} = 0.22(R_{e_{\theta l}})^{-1} \left(\frac{\rho^*}{\rho_e}\right) \left(\frac{\mu^*}{\mu_e}\right) \rho_e V_e (H_{aw} - H_w) (Pr_w)^{-0.6} \quad (10)$$

The variable of p^* and μ^* are introduced to consider the compressibility effects. These variables are evaluated at the Eckert's reference enthalpy [15] defined as:

$$H^* = 0.50 H_e + 0.50 H_w + 0.22R \frac{V_e^2}{2} \quad (11)$$

The laminar boundary layer momentum thickness is:

$$\theta_L = \frac{0.644[\int_0^s \rho^* \mu^* V_e r^2 ds]^{1/2}}{\rho_e V_e r} \quad (12)$$

The adiabatic wall enthalpy is defined as:

$$H_{aw} = H_e + 0.5 R V_e^2 \quad (13)$$

Similar equations are developed for the turbulent flow [14]:

$$q_{wT} = C_1 (R_{e_{\theta T}})^{-m} \left(\frac{\rho^*}{\rho_e}\right) \left(\frac{\mu^*}{\mu_e}\right)^m \rho_e V_e (H_{aw} - H_w) (Pr_w)^{-0.4} \quad (14)$$

$$\theta_T = \frac{c_1 [\int_0^s \rho^* \mu^* V_e r^{c_2} ds]^{c_4}}{\rho_e V_e r} \quad (15)$$

The coefficients of m, C_1, C_2, C_3 and C_4 are functions of N and experimental results show that N would be a function of $Re_{\theta T}$, and are given by:

$$m = \frac{2}{N+1}, \quad C_1 = \left(\frac{1}{C_5}\right)^{\frac{2N}{N+1}} \left[\frac{N}{(N+1)(N+2)}\right]^m$$

$$c_2 = (1+m)c_1, \quad C_3 = 1+m$$

$$C_4 = \frac{1}{C_3} \quad c_5 = 2.2433 + 0.93N$$

$$N = 12.67 - 6.5 \log(Re_{\theta T}) + 1.21 [\log(Re_{\theta T})]^2$$

The heating rates can be calculated on the surface of body, from either equation 10 or equation 14. The values of pressure, temperature, density and the velocity magnitude at the edge of the boundary (i.e. P_e, T_e, ρ_e and V_e) are calculated from the present method and commercial CFD codes.

IV. RESULTS

The numerical results of this method are compared with other numerical methods results and experimental results. The shock shape over a parabola blunted nose for $M_\infty = 10$ and $\gamma = 1.4$ are shown in Fig 2. The results obtained from the present approach are compared with those of ref.16. Good agreement between the results of the present method and experimental data is shown in Fig 2. The pressure distribution over spherically blunted nose is shown this Fig 3. These results are compared with pressure distribution ref 16 and ref. 17. Also compares between the aero heating results of the present method, commercial CFD code data and results ref. 18 is shown in Fig 4 (within 10%). The Mach number and temperature Contours are shown in Fig 5 and Fig 6.




Fig. 2 Shock shape




Fig. 3 Pressure distribution on parabola at $M_\infty=10$ and $\gamma=1.4$




Fig. 4 Convection heating distribution parabola at $TW=1256$



Fig. 5 Contours of Mach number for parabola at $M_\infty=10$ and $\gamma=1.66$




Fig. 6 Contours of Temperature for parabola at $M_\infty=10$ and $\gamma=1.66$

In Fig. 7, the shock shape over an elliptic blunted nose for $M_\infty=8.08$ and $\gamma=1.4$ is shown. The pressure distribution is shown in Fig. 8.

The convection heating rate over a ellipsoid blunted nose for $M_\infty=8.08$ and $\gamma=1.4$ are shown in Fig 9. These results are compared with results ref 20 and 21. In this comparison, there is an error of less than 10% noted. Good agreement between the results of the present method and commercial CFD code data is shown in Fig 9(less than 8% disagreement), the maximum qst in Fig 4 is 49343.44(MW/m²).

The commercial CFD code output results are shown in fig 10 and fig 11. These figures are related to contours of Mach and temperature.




Fig. 7 Shock shape




Fig. 8 Pressure distribution on ellipsoid at $M_\infty=8.08$ and $\gamma=1.4$




Fig. 9 Convection heating distribution ellipsoid at $TW=1586.89$




Fig. 10 Contours of Mach number for ellipsoid at $M_\infty=8.08$ and $\gamma=1.4$




Fig. 11 Contours of Temperature for ellipsoid at $M_\infty=8.08$ and $\gamma=1.4$

V. CONCLUSION

A conclusion section is not required. Although a conclusion may review the main points of the paper, do not replicate the abstract as the conclusion. A conclusion might elaborate on the importance of the work or suggest applications and extensions.

REFERENCES

- [1] Shaw ST, Shan C. and Qin N. Development of a local MQ-DQ-based stencil adaptivemethod and its application to solve incompressible Navier-Stokes equations. Int J Numer Meth Fluids, Vol. 55, Issue 4, pp367 – 386, 2007.
- [2] Shaw S.T. and Qin N. Solution of the Navier-Stokes equations for the flow around anaerofoil in oscillating free stream. Proceeding of the 20th Congress of the International Council of the Aeronautical Sciences, ICAS, Vol.1, pp19-29. ISBN 1-56347-219-8, 1996.
- [3] Scalabrin L.C. and Boyad L.D. Development of an unstructured Navier-Stokes for hypersonic nonequilibrium aerothermodynamics. 38th AIAA Thermo physics Conference, June 2005.
- [4] Birch T., Prince S., Ludlow D.K and Qin N. The application of a parabolized Navier-Stokes solver to some hypersonic flow problems. AIAA 1753- 2001.
- [5] Esfahanian V., Hejranfar K. and Mahmoodi Darian, H. Implementation of high-order compact finite-difference method to iterative parabolized Navier-Stokes equations.
- [6] Proceedings of the 25th International Congress of the Aeronautical Sciences, ICAS2006, Hamburg, Sept, 2006.
- [7] Noori S., Ghasemloo S. and Mani M. A., new method for solution of viscous shock layer equations. Journal of Aerospace Engineering, Vol. 224, part G, 2010.

- [8] Miner E. W. and Lewis C. H., Hypersonic ionizing air viscous shock-layer flows over nonanalytical blunt bodies. NASA CR-2550, May 1975.
- [9] Kuchi-Ishi S. The development of a new viscous shock-layer code for computing hypersonic flow around blunted body and Its applications. JAXA Research and Development Report, RR-05-001E, 2005.
- [10] Thompson R. A., Comparison of nonequilibrium viscous shock-layer solutions with shuttle heating measurements. Journal of Thermophysics and Heat Transfer, Vol.4, No. 2, PP. 162-169, 1990.
- [11] Hamilton H. H., Greene F. A. and DeJarnette F. R., An approximate method for calculating heating rates on three-dimensional vehicles. AIAA paper 93-2881, 1993.
- [12] Zoby E. V. and simmonds A. L., Engineering flow field method with angle-of-attack applications. Journal of spacecraft and rockets, Vol. 22, No. 4, PP.398-405, 1985.
- [13] Hamilton H. H., Greene F. A. and DeJarnette F. R. Approximate method for calculating heating rates on three-dimensional Vehicles. Journal of Spacecraft and rockets. Vol.31. No. 3, pp. 345-354. 1994.
- [14] Maslen S.H. Inviscid hypersonic flow past smoth symmetric bodies. AIAA Journal, Vol. pp.1055-1061, 2, July 1964.
- [15] Zoby E. V, Moss J. J and Sutton K. Approximate convective-heating equations for hypersonic flows. Journal of Spacecraft and Rockets, Vol. 18, No.1, pp.64-70, 1981.
- [16] Eckert E.R.G. Engineering relations for friction and heat transfer to surfaces in high velocity flow. Journal of the Aeronautical Sciences, Vol.22, No.8, pp. 585-587, 1955.
- [17] Van Dyke, Milton D, and Gordon, Helen D. Supersonic flow past a family of blunt axisymmetric bodies. NASA TR R-1, 1959.
- [18] Holt M and Hoffman G. Calculation of hypersonic flow past sphere and ellipsoids. American Rocket Soc., 61-209-1903., June 1961.
- [19] Mitcheltree R. A, DiFulvio M, Horvath T. J and Braun R. D. Aero thermal heating predictions for mars microprobe. AIAA paper 98-0170, 1998.
- [20] Murray A. L and Lewis C. H., Hypersonic three-dimensional viscous shock layer flows over blunt bodies. AIAA Journal, Vol. 16: pages 1279-1286, December 1978.
- [21] Hollis B. R. and Perkins J. N. High enthalpy and perfect gas heating measurements on blunt cone. Journal of Spacecraft and Rockets, Vol. 33, No.5, pp.628-634, 1996.
- [22] Miller III. C. G. Measured pressure distributions, aerodynamic coefficients, and shock shapes on blunt bodies at Incidence in Hypersonic Air and CF4. NASA TM-84489, Sept, 1982.